

# High-current test probe

## HSS-118 306 350 A 1508

Item HSS-118-0260






GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology

- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-resistance contact probe with Ri typical < 10 mΩ
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights



### General data

Product group:  
Sub-product group:  
Series:  
Grid:  
Contacting from:  
Magnetic:  
Installation type:  
Quick-exchange system:  
Adjustable installation height:  
Non-rotating:  
Compatible receptacle(s):  
Min. temperature:  
Max. temperature:  
RoHS-compliant:

Standard HSS (press-in)  
Standard HSS (press-in)  
HSS-118  
4 mm [157 mil]  
Post  
Yes  
Plug-in  
Yes  
No  
No  
KS-112  
-100 °C [-148 °F]  
200 °C [392 °F]  
Yes

### Tip style data

Tip style:  
Tip diameter:  
Tip style surface:  
Tip style material:

06 serrated  
3.5 mm [.137 in]  
A gold  
3 CuBe

### Electrical data

Current load capacity / rated current:  
Typical resistance (Ri):

20 A  
10 mOhm

### Mechanical data

Total length:  
Barrel diameter:  
Maximum stroke:  
Spring pre-load:  
Collar height:  
Spring force at working stroke:  
Recommended working stroke:

38.3 mm [1.5 in]  
1.66 mm [.065 in]  
5.3 mm [.208 in]  
0.5 N [1.79 ozf]  
08  
1.5 N [5.39 ozf]  
4 mm [.157 in]


# High-current test probe HSS-118 306 350 A 1508

Item HSS-118-0260



**ingun**<sup>®</sup>

Partner for Future Technology



## INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 05/26\_GB

Learn more about  
High-current test probes



ingun.com