





GO TO PRODUCT

- Robust, compact design for harsh ICT/FCT applications with limited space
- For optimum contact at the test points (e.g. pads, vias, and pins), various tip styles in different diameters and finishes, as well as various spring forces are available. spring forces.



1:1



General data

Product group:	ICT / FCT (in-circuit test and function test)
Sub-product group:	Short/robust GKS
Series:	GKS-005
Grid:	4.75 mm [187 mil]
Contacting from:	Pad
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-005
Min. temperature:	-40 °C [-40 °F]
Max. temperature:	80 °C [176 °F]
RoHS-compliant:	Yes

Tip style data

Tip style:	01 30° needle tip, self-cleaning
Tip diameter:	2.03 mm [.079 in]
Tip style surface:	A gold
Tip style material:	2 steel

Electrical data

Current load capacity / rated current:	6 A
Typical resistance (Ri):	20 mOhm

Mechanical data

Total length:	36.1 mm [1.42 in]
Maximum stroke:	6.35 mm [.25 in]
Spring pre-load:	2.38 N [8.56 ozf]
Collar height:	00
Spring force at working stroke:	5 N [17.9 ozf]
Recommended working stroke:	4.4 mm [1.73 in]

Test Probe


GKS-005 201 203 A 5000

Item GKS-005-0008



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 06/26_GB

Learn more about
ICT/FCT Test probes



ICT/FCT TEST PROBES

ingun.com