

Vacuum seal

VD-V-VA4060T-2

Item 114555



GO TO PRODUCT

ingun[®]

Partner for Future Technology

- Outstanding service life
- Wartungsarm
- Zuverlässige Abdichtung, für stabile, reproduzierbare Kontaktierungen

Application

Vakuumdichtungen werden in Vakuum-Prüfadaptern verwendet, um ein prozessstabiles Vakuum zu erzeugen, zur Durchführung zuverlässiger Tests (ICT/FCT) an elektronischen Leiterplatten.



General data

Product group: Spare part kits
 Series: VD-VAxxxx
 Type: Outer vacuum seal VAxx60T
 Version: Fixed outer dimensions
 Accessory type: Spare parts
 Scope of delivery: Unassembled
 Width: 308 mm [12.1 in]
 Height: 21 mm [.826 in]
 Weight: 0.15 kg [.33 lbs]
 Min. temperature: 10 °C [50 °F]
 Max. temperature: 60 °C [140 °F]
 RoHS-compliant: Yes

Compatible with

Vacuum test fixtures (VA): VA 4060T

Technical data

Useable area (WxD): 225 x 430 mm [8.85 x 16.9 in]
 Length: 528 mm [20.7 in]
 Outer dimensionS (WxDxH): 308 x 528 x 21 mm [12.1 x 20.7 x .826 in]

Vacuum test fixtures

Part no. EN	Designation	Tip version EN
114638	VA 4060T/D/H	Vacuum test fixture
114662	VA 4060T/D/H/MTS300	Vacuum test fixture
114625	VA 4060T/D/H/PYLON-12	Vacuum test fixture
114668	VA 4060T/D/H/MPC-G12	Vacuum test fixture
114632	VA 4060T/F/H	Vacuum test fixture
114650	VA 4060T/F/H/GR2270/71	Vacuum test fixture
114660	VA 4060T/F/H/GR228x15/07	Vacuum test fixture
114655	VA 4060T/F/H/GR228x15/15	Vacuum test fixture
114619	VA 4060T/F/H/PYLON-12	Vacuum test fixture
114678	VA 4060T/F/H/VPC-G12	Vacuum test fixture

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
 78467, Constance, Germany
 Phone +49 7531 8105-0
 Customer hotline +49 7531 8105-888
 Fax +49 7531 8105-65
 info@ingun.com



Learn more about
Test fixture kits

