

Detection DUT present FB-ABF-A-O-10-30VDC

Item 116667




ingun[®]

Partner for Future Technology

- Detection of PCB - present
- Functional unit for individually configurable upgrade
- Suitable for inline interchangeable kits WS ASYS/ATH01/173,5 and WS ASYS/ATH01/210,5
- Quick, easy installation on the pressure frame plate

Application

Detection units are used to detect various states and manage essential control tasks. The detection unit is a functional unit for individually configurable upgrade and is used to detect the presence of the PCB. It is used with inline interchangeable kits WS ASYS/ATH01/173.5 and WS ASYS/ATH01/210.5.



General data

Product group:	Functional units
Series:	FB-WS
Type:	Detection unit
Version:	DUT detection, photoelectric sensor
Accessory type:	Additional function
Scope of delivery:	Must be installed upon delivery, installation accessories included
Width:	28 mm [1.1 in]
Height:	25 mm [.984 in]
Weight:	0.02 kg [.044 lbs]
Min. temperature:	10 °C [50 °F]
Max. temperature:	60 °C [140 °F]
RoHS-compliant:	Yes

Compatible with

Interchangeable kits (WS): WS ASYS/ATH01/...

Technical data

Installation:	Thread M3
Max. voltage:	30 VDC
Length:	41.8 mm [1.64 in]
Cable length:	2000 mm [78.7 in]
Outer dimensionS (WxDxH):	41.8 x 28 x 25 mm [1.64 x 1.1 x .984 in]


Detection DUT present FB-ABF-A-O-10-30VDC

Item 116667



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 05/26_GB

Learn more about
WS functional units

