

# Electric proximity switch

## ENS-I-D03-S-0,6-10-30V-K2,0

Item 25263



GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology


- Berührungslos wirkend
- Präziser Schalterpunkt
- Robust gegen Staub, Feuchtigkeit und Erschütterungen
- Schaltabstand: 0,6 mm

### Application

Näherungsschalter werden zur Erkennung von Positionen eingesetzt, um Prozesse zu steuern oder Zustände zu überwachen. Sie wirken berührungslos.



1:1



### General data

Product group:  
Series:  
Type:  
Version:  
Accessory type:  
Weight:  
Min. temperature:  
Max. temperature:  
RoHS-compliant:

Electric accessory  
ENS  
Proximity switch, inductive  
Customising accessories  
0.01 kg [0.022 lbs]  
-25 °C [-13 °F]  
80 °C [176 °F]  
Yes

### Compatible with

Accessories:

SBE-O-08-04-S2,5-BW1,8

### Technical data

Connection:  
Max. current:  
Installation:  
Max. voltage:  
Length:  
Diameter:  
Cable length:

Cable  
0.2 A  
Clamped in bore  
30 VDC  
12 mm [0.472 in]  
3 mm [0.118 in]  
2000 mm [78.7 in]

### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 06/26\_GB