

Test Probe

GKS-002 201 107 A 1000

Item GKS-002-0001



GO TO PRODUCT


ingun[®]

Partner for Future Technology


- Robust, compact design for harsh ICT/FCT applications with limited space
- For optimum contact at the test points (e.g. pads, vias, and pins), various tip styles in different diameters and finishes, as well as various spring forces are available. Spring forces.



INGUN SELECTION



1:1



General data

Product group:	ICT / FCT (in-circuit test and function test)
Sub-product group:	Short/robust GKS
Series:	GKS-002
Grid:	2.54 mm [100 mil]
Contacting from:	Pad
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-002
Min. temperature:	-40 °C [-40 °F]
Max. temperature:	80 °C [176 °F]
RoHS-compliant:	Yes

Tip style data

Tip style:	01 30° needle tip, self-cleaning
Tip diameter:	1.07 mm [.042 in]
Tip style surface:	A gold
Tip style material:	2 steel

Electrical data

Current load capacity / rated current:	5 A
Typical resistance (Ri):	20 mOhm

Mechanical data

Total length:	24.6 mm [.968 in]
Barrel diameter:	1.37 mm [.053 in]
Maximum stroke:	4.1 mm [.161 in]
Spring pre-load:	0.49 N [1.76 ozf]
Collar height:	00
Spring force at working stroke:	1 N [3.59 ozf]
Recommended working stroke:	2.7 mm [.106 in]

Test Probe

GKS-002 201 107 A 1000


Item GKS-002-0001



GO TO PRODUCT

ingun®

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 06/26_GB

Learn more about
ICT/FCT Test probes



ingun.com