





- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture:  
The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights



1:1



### General data

|                                 |   |
|---------------------------------|---|
| Product group:                  | ICT / FCT (in-circuit test and function test) |
| Sub-product group:              | Metric standard                               |
| Series:                         | GKS-412                                       |
| Grid:                           | 2.54 mm [100 mil]                             |
| Contacting from:                | Pad   |
| Magnetic:                       | Yes   |
| Installation type:              | Plug-in                                       |
| Quick-exchange system:          | Yes   |
| Adjustable installation height: | No  |
| Non-rotating:                   | No  |
| Compatible receptacle(s):       | KS-112  |
| Min. temperature:               | -40 °C [-40 °F]                               |
| Max. temperature:               | 80 °C [176 °F]                                |
| RoHS-compliant:                 | Yes   |

### Tip style data

|                     |                                |
|---------------------|--------------------------------|
| Tip style:          | 09 flexi-needle, self-cleaning |
| Tip diameter:       | 0.7 mm [.027 in]               |
| Tip style surface:  | N nickel                       |
| Tip style material: | 2 steel                        |

### Electrical data

|  |         |
|--|---------|
| Current load capacity / rated current: | 5 A     |
| Typical resistance (Ri):               | 20 mOhm |

### Mechanical data

|                                 |                   |
|---------------------------------|-------------------|
| Total length:                   | 37.8 mm [1.48 in] |
| Barrel diameter:                | 1.66 mm [.065 in] |
| Maximum stroke:                 | 9.8 mm [.385 in]  |
| Spring pre-load:                | 0.75 N [2.69 ozf] |
| Collar height:                  | 02                |
| Spring force at working stroke: | 5 N [17.9 ozf]    |
| Recommended working stroke:     | 8 mm [.314 in]    |

# Test Probe

## GKS-412 209 070 N 5002


Item GKS-412-0080



GO TO PRODUCT

# ingun®

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 05/26\_GB

Learn more about  
ICT/FCT Test probes



ingun.com