



GO TO PRODUCT

- Parallel closing drive unit with mounting plate, without internal interface
- High contact force
- Freely configurable signal transmission with VG multipoint connector
- Quick, easy, precise installation
- Can be used for various applications

INGUN SELECTION



General data

Product group:	Manual drive unit
Main series:	ATE MAxxx
Series:	ATE MA3xx
Size:	350
Test fixture type:	With mounting plate
Contact stroke generation:	Manual
Max. interface signals:	150
Interface blocks required:	No
Max. contact force:	300 N [1,079 ozf]
Approx. parallel contact stroke:	20 mm [.787 in]
Min. temperature:	10 °C [50 °F]
Max. temperature:	60 °C [140 °F]
RoHS-compliant:	Yes

Technical data

Force of gas pressure springs:	100 N
Pressure frame opening angle:	65 °
Outer dimensions, open (WxDxH):	145 x 140 x 310 mm [5.7 x 5.51 x 12.2 in]
Outer dimensions, closed (WxDxH):	145 x 345 x 174 mm [5.7 x 13.5 x 6.85 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Learn more about
Test fixture kits

