

# Top interchangeable kit WSO SPEA/3030/OL/PAS

Item 52534-KIT



GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology

- Trusted interchangeable kits for SPEA inline test systems
- Precise, reliable contacting with peRfectly configured guides
- Modular design with bottom interchangeable kit (WSU) and top interchangeable kit (WSO)
- Robust, durable design with outstanding service life



## General data

Product group:	Inline interchangeable kit (WS)
Subseries:	SPEA 3030
Series:	WS SPEA-3030
Version:	With interface
Scope of delivery:	Unassembled
Weight:	5.5 kg [12.1 lbs]
Min. temperature:	10 °C [50 °F]
Max. temperature:	60 °C [140 °F]

## Technical data

Pushrod length:	96.2 mm [3.78 in]
Test probe installation height, top:	15 mm [.59 in]
Test probe installation height, bottom:	13 mm [.511 in]
Test probe installation height, dual-stage, bottom:	18.3 mm [.72 in]
Useable area (WxD):	500 x 300 mm [19.6 x 11.8 in]
Outer dimensionS (WxDxH):	597 x 410 x 116 mm [23.5 x 16.1 x 4.56 in]

## INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 05/26\_GB

Learn more about  
Inline interchangeable kit



INLINE INTERCHANGEABLE KITS

ingun.com