

Gas pressure spring

GDF-305-120-300N-A6-A6

Item 9991



GO TO PRODUCT



ingun[®]

Partner for Future Technology

- Trusted gas springs from the market leader
- Store with the piston rod facing downwards

Note:

The gas springs must be stored with the piston rod pointing downwards so that the seal remains moistened from the inside. It makes no difference whether the piston of the gas spring is extended (unloaded) or retracted (loaded).



General data

Product group:
Series:
Type:
Version:
Accessory type:
Min. temperature:
Max. temperature:
RoHS-compliant:

Gas springs
GDF
Gas spring
Standard, attenuated
Spare parts
10 °C [50 °F]
60 °C [140 °F]
Yes

Technical data

Stroke:
Force:
Length:
Gas pressure spring length, home position:
Plunger length, home position:
Installation 1 diameter:
Installation 2 diameter:

120 mm [4.72 in]
300 N [1,079 ozf]
305 mm [12 in]
185 mm [7.28 in]
127 mm [5 in]
6 mm [.236 in]
6.2 mm [.244 in]



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 06/26_GB