





GO TO PRODUCT

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture: The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Stainless steel versions for temperatures from -100 °C up to +200 °C available



1:1



### General data

Product group:  
 Sub-product group:  
 Series:  
 Grid:  
 Contacting from:  
 Magnetic:  
 Installation type:  
 Quick-exchange system:  
 Adjustable installation height:  
 Non-rotating:  
 Compatible receptacle(s):  
 Min. temperature:  
 Max. temperature:  
 RoHS-compliant:

ICT / FCT (in-circuit test and function test)  
 Metric standard  
 GKS-113  
 4 mm [157 mil]  
 Post  
 Yes  
 Plug-in  
 Yes  
 No  
 No  
 KS-113  
 -40 °C [-40 °F]  
 80 °C [176 °F]  
 Yes

### Tip style data

Tip style: 06 serrated  
 Tip diameter: 1.6 mm [.062 in]  
 Tip style surface: A gold  
 Tip style material: 3 CuBe

### Electrical data

Current load capacity / rated current: 8 A  
 Typical resistance (Ri): 30 mOhm

### Mechanical data

Total length: 27.3 mm [1.07 in]  
 Barrel diameter: 2.65 mm [.104 in]  
 Maximum stroke: 5.3 mm [.208 in]  
 Spring pre-load: 0.75 N [2.69 ozf]  
 Collar height: 02  
 Spring force at working stroke: 2.25 N [8.09 ozf]  
 Recommended working stroke: 4 mm [.157 in]

# Test Probe

## GKS-113 306 160 A 2202


Item GKS-113-1302



GO TO PRODUCT

# ingun®

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 06/26\_GB

Learn more about  
ICT/FCT Test probes



ingun.com