

Test Probe

GKS-713 256 225 R 5007


Item GKS-713-0016






GO TO PRODUCT

ingun[®]

Partner for Future Technology



1:1



General data

Product group:	ICT / FCT (in-circuit test and function test)
Sub-product group:	Rotating test probes
Series:	GKS-713
Grid:	4.5 mm [177 mil]
Contacting from:	Post
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	No
Type of test probe connection:	Plug
Adjustable installation height:	No
Non-rotating:	No
Continuous plunger:	$\phi 1,3 \times 10,0$
Compatible connector(s):	SE-503
Compatible receptacle(s):	KS-713
Min. temperature:	-100 °C [-148 °F]
Max. temperature:	200 °C [392 °F]
RoHS-compliant:	Yes

Tip style data

Tip style:	56 serrated, special length
Tip diameter:	2.25 mm [.088 in]
Tip style surface:	R rhodium
Tip style material:	2 steel

Electrical data

Current load capacity / rated current:	5 A
Current rating, connection on plunger:	8 A
Typical resistance (Ri):	100 mOhm
Typical resistance (Ri), connection on plunger:	10 mOhm

Mechanical data

Total length:	40 mm [1.57 in]
Barrel diameter:	2.65 mm [.104 in]
Maximum stroke:	5 mm [.196 in]
Spring pre-load:	1.25 N [4.49 ozf]
Collar height:	07
Spring force at working stroke:	5 N [17.9 ozf]
Recommended working stroke:	4 mm [0.157 in]

Test Probe

GKS-713 256 225 R 5007


Item GKS-713-0016



GO TO PRODUCT

ingun®

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 05/26_GB

Learn more about
ICT/FCT Test probes



ingun.com

ICT/FCT TEST PROBES