

Receptacle KS-002 30 G


Item KS-00230G




GO TO PRODUCT

ingun[®]

Partner for Future Technology



1:1



General data

Product group:
Series:
Sub-series:
Type of receptacle connection:
Press ring:
Surface area:
Collar diameter:
Collar height:
Knurl:
Vacuum-tight:
RoHS-compliant:

Receptacles (KS)
KS-002
KS-002 press-in version
Solder
Yes
Gold
1.78 mm [.07 in]
6.1 mm [.24 in]
No
No
Yes

Mechanical data

Total length: 24.2 mm [.952 in]
Outer diameter: 1.67 mm [.065 in]

Mounting hole

Mounting hole in CEM1: 1.68 - 1.69 mm [.066 in]
Mounting hole in FR4: 1.68 - 1.69 mm [.066 in]
Mounting hole with press ring in CEM1: 1.7 - 1.75 mm [.066 - .068 in]
Mounting hole with press ring in FR4: 1.7 - 1.75 mm [.066 - .068 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 06/26_GB

Learn more about
Test probes

