

Test plug PS-USB3.1C-F-024-G5-B-02

Item 116807




GO TO PRODUCT

ingun[®]

Partner for Future Technology

- Precise, low-wear contacting of USB plug connectors
- Outstanding service life
- Reliable data transmission
- Signal transmission to the test system via original connector plug or solder connection
- Optional spring elements (112863: set of 2) can compensate for tolerances of ± 0.4 mm and positioning inaccuracies.

INGUN SELECTION



- M3x8 T10 (2x)
- M1x4 (4x)
- reducing washer (2x)

Test plug

PS-USB3.1C-F-024-G5-B-02

Item 116807

GO TO PRODUCT

ingun[®]

Partner for Future Technology

General data

Product group:	PS test plug
Series:	PS
Sub-series:	PS-USB
Grid:	8 mm [314 mil]
DUT / contact:	USB3.1-C
DUT interface gender :	M signal conductor male / pin
Continuous plunger:	No
Interface of compatible assembly:	USB 3.1-C
Compatible assembly interface gender :	M signal conductor male / pin
Width:	30 mm [1.18 in]
Height:	7 mm [.275 in]
Min. temperature:	-20 °C [-4 °F]
Max. temperature:	75 °C [167 °F]
RoHS-compliant:	Yes

Inner conductor data






Exchangeable inner conductor:	No
Inner conductor max. current load capacity:	3 A
Number of inner conductor poles:	24

Electrical data

Impedance:	90 Ohm
Max. data rate:	10 Gbit/s
Maximum performance:	15 W

Mechanical data

Total length:	27 mm [1.06 in]
Installation height without receptacle:	18.25 mm [.718 in]



Test plug

PS-USB3.1C-F-024-G5-B-02

Item 116807

[GO TO PRODUCT](#)

ingun[®]

Partner for Future Technology

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 06/26_GB

Learn more about
Test probes

