




**INGUN SELECTION**



**General data**

Product group:  
Sub-product group:  
Series:  
Grid:  
Contacting from:  
Magnetic:  
Installation type:  
Quick-exchange system:  
Adjustable installation height:  
Non-rotating:  
Compatible receptacle(s):  
Min. temperature:  
Max. temperature:  
RoHS-compliant:

ICT / FCT (in-circuit test and function test)  
Fine-pitch  
GKS-069  
1.27 mm [50 mil]  
Post  
Yes  
Plug-in  
Yes  
No  
KS-069  
-40 °C [-40 °F]  
80 °C [176 °F]  
Yes

**Tip style data**

Tip style:  
Tip diameter:  
Tip style surface:  
Tip style material:

06 serrated  
0.9 mm [.035 in]  
A gold  
3 CuBe

**Electrical data**

Current load capacity / rated current:  
Typical resistance (Ri):

3 A  
20 mOhm

**Mechanical data**

Total length:  
Barrel diameter:  
Maximum stroke:  
Spring pre-load:  
Collar height:  
Spring force at working stroke:  
Recommended working stroke:

16.5 mm [.649 in]  
0.69 mm [.027 in]  
2.8 mm [.11 in]  
0.42 N [1.51 ozf]  
00  
0.7 N [2.51 ozf]  
2.2 mm [.086 in]

# Test Probe


## GKS-069 306 090 A 0700

Item GKS-069-0037



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 05/26\_GB

Learn more about  
ICT/FCT Test probes



ingun.com